

641 SERIES


The 641 offers panel finishes for the ultimate in design flexibility. Even the frames may be color matched to coordinate with the faces. The 641 is a popular choice for hotel meeting rooms, convention centers, commercial facilities, or other high use facilities.

INDIVIDUAL, OMNI-DIRECTIONAL PANELS





TYPE 2



TYPE 3

*Contact Gibca for other available options

Individual, manually operated panels offer optimum room flexibility. The track system enables panels to negotiate turns and be used in alternate locations. The panels are nominally 4" [102] thick and have a welded 16 ga. Steel frame.



Top Supported

Side Stack

Individual, Omni-Directional

Panels

Manually Operated

Maximum Height: 40'5"

[12.3m] *

Maximum Opening Width:

Unlimited

STC Ratings: 43, 47, 49, 52,

54, 55, 56

56STC rating can be achieved with special construction

*Taller heights are available. Contact Gibca for assistance.

Available Accessories/Options

- Pass Door Inclusion Options Exit signs, Automatic door closers, panic hardware, locks, frame and prep for window, peep viewer
- Pocket Doors for Partition Storage factory-finished or field-finished
 Work Surface Inset or full-height dry erase steel marker boards, inset porcelain
- Work Surface Inset or full-height dry erase steel marker boards, inset porcelair enamel steel dry marker or chalkboard, eraser pocket or tack boards
- Acoustic Baffle

Suspension System

For panels weighing up to 1500 lbs. [680 kg]: Track shall be of clear anodized architectural grade extruded aluminum alloy 6063-T6.

For panels weighing over 1500-3000 lbs. [680-1364 kg]: Track shall be of 1/4" [6] formed black painted steel. Carriers may be programmed for self directing and sorting.

Trim Colors - standard

Available in three standard trim colors - lamb's wool, Brown or Gray. Custom colors for metal trim are also available for an additional charge.

"Standard" Product Features and Benefits:

Feature: Protective vertical trim (Available option: no protective vertical face trim.) Benefit: Trim protects the panel edges and faces plus it

- Senefit: Trim protects the panel edges and faces plus it provides a handhold when moving panels.
- Feature: Quick-Set™ Retractable Seals.
- **Benefit:** The retractable seals are Quick-Set[™] which means they are easily extended or retracted with only a 1/2 turn of the removable handle. No tedious cranking needed to set the seals.
- Feature: 2" [51] retractable bottom seals
- Benefit: Retractable seals accommodate out-of-level floor conditions. When retracted, nothing drags on the floor when the panels are moved. Panels can be "locked" in place.
- Feature: Retractable seals exert upward and downward seal force
- **Benefit:** Provides constant force against the track and floor for optimum acoustics even on carpet or other porous floor materials. Maintains panel stability when the seals are set.
- Feature: Waist high seal activator for quick set retractable seals.
- Benefit: Fast, easy seal activation without bending or stooping.
- **Feature:** Removable operating handle. **Benefit:** Prevents unauthorized operation.
- Feature: Expanding Jamb Closure (Lever Closure) Panel Benefit: Exerts 250 lbs [113.4 kg] of force against the fixed wall. The compression creates tight panel joints for optimum sound control.

Feature: Interlocking vertical seals Benefit: Ensures panel-to-panel alignment and prevents sound leaks between panels.





Finishes:

Face finish shall be:

- Factory applied reinforced vinyl/fabric with woven backing.

- -Optional:
 - 1. Custumer Selected
 - 2. Unfinished for field decoration.
 - 3. Wood Veneer
 - 4. High pressure laminate

